

defining warehouse zones.

Our modular rails and bollards allow for damaged or worn parts to be replaced at a component level. If you need to replace any component - it is just a slide away.



X-Protect is a unique approach to safety barriers. Unrivalled modularity, using only a few system components and damping that is built in to create a barrier system that changes with your work place. X-Protect allows rapid transformation, repair or replacement of existing barriers and bespoke configurations are limitless.

Impact test results	S				
Area of impact	Load	Equivalent to	Equivalent to		Force to fixings
Centre of barrier C	: - C as below			·	
2000mm	6200 J	2500 kg 8 km/h	5000 kg 5.6 km/h	430mm	14.5 kN
2500mm	5500 J	2500 kg 7.5 km/h	5000 kg 5.3 km/h	470mm	12.2 kN

3000mm	15.71111		5000 kg 5.1 km/h	520mm	10.4 kN
Posts					
End post			5000 kg 3.5 km/h	NA *	19.2 kN
Mid post			5000 kg 3.5 km/h	NA *	18.1 kN

^{*} Deflection of posts is equivalent or less than that of the rail/s and is not considered to be critical for product selection. Performance is tested at height of the lowest rail. The post will perform better for lower strikes and deflection.

Models

Posts 6 articles

ARTICLES / DESC	RIPTION	HEIGHT (MM)	LENGTH (MM)	CC (MM)	COLOR
1	BCC1-061-I100 Impact High corner	610			Zinc Yellow
•	BCC0-061-I100 Impact High corner	610			Zinc Yellow Graphite Black
1	BCM1-061-I100 Impact High mid	610			Zinc Yellow
1	BCM0-061-I100 Impact High mid	610			Zinc Yellow Graphite Black
	BCE1-061-I100 Impact High end	610			Zinc Yellow
	BCE0-061-I100 Impact High end	610			Zinc Yellow Graphite Black

Impact rails 15 articles

HEIGHT (MM)	LENGTH (MM)	CC (MM)	COLOR
	2770	3000	Zinc Yellow
	2270	2500	Zinc Yellow
	1770	2000	Zinc Yellow
	1270	1500	Zinc Yellow
	770	1000	Zinc Yellow
	470	700	Zinc Yellow
	270	500	Zinc Yellow
	640	870	Zinc Yellow
	670	900	Zinc Yellow
	1970	2200	Zinc Yellow
	2010	2240	Zinc Yellow
	740	970	Zinc Yellow
	2070	2300	Zinc Yellow
	2110	2340	Zinc Yellow
	2170	2400	Zinc Yellow
	HEIGHT (MM)	2770 2270 1770 1270 770 470 270 640 670 1970 2010 740 2070	2770 3000 2270 2500 1770 2000 1270 1500 770 1000 470 700 270 500 640 870 1970 2200 2010 2240 740 970 2070 2300 2110 2340

Related products

IMPACT BARRIERS



Impact

Use the X-Protect Impact Barrier for ground level impact protection. It is ideal for segregating light weight vehicles or defining warehouse zones. Our modular rails and bollards allow for damaged...

21 articles



IMPACT BARRIERS

Double impact

Use the X-Protect Double Impact Barrier configuration to protect structures from high level, heavy duty impacts. It is one of our strongest Impact protection configurations. Our modular rails and b...

21 articles



IMPACT BARRIERS

Double impact low

Use the X-Protect Double Impact Low Barrier configuration to protect structures from ground level, heavy duty impacts. It is one of our strongest Impact protection configurations and also ideal for...

21 articles



PEDESTRIAN BARRIERS

Pedestrian with impact high

Use the X-Protect Pedestrian + Impact high barrier configuration to protect walkways from medium duty vehicles where there is a reduced risk of ground level impacts. It is also possible to combine...

19 articles