

also possible to combine with a pedestrian gate. The pedestrian gate is self closing, provided with a universal handle and width is adjustable from 690-1210 mm.



X-Protect is a unique approach to safety barriers. Unrivalled modularity, using only a few system components and damping that is built in to create a barrier system that changes with your work place. X-Protect allows rapid transformation, repair or replacement of existing barriers and bespoke configurations are limitless.

Impact test results						
Area of impact	Load	Equivalent to		90° Deflection	Force to fixings	
Centre of barrier C -	Centre of barrier C - C as below					
1500mm	4000 J	2500 kg 6.4 km/h	5000 kg 4.5 km/h	360mm	14.3 kN	
2000mm	5000 J	2500 kg 7.2 km/h	5000 kg 5 km/h	490mm	18.7 kN	
Posts	Posts					
End post	1900 J	2500 kg 4.4 km/h	5000 kg 3.1 km/h	NA *	10 kN	
Mid post	1900 J	2500 kg 4.4 km/h	5000 kg 3.1 km/h	NA *	8.4 kN	

^{*} Deflection of posts is equivalent or less than that of the rail/s and is not considered to be critical for product selection. Performance is tested at height of the lowest rail. The post will perform better for lower strikes and deflection.

Models

Posts 6 articles

ARTICLES / DESCRIPTION		HEIGHT (MM)	CC (MM)	COLOR
<u>:</u>	BCC1-116-00P3 Pedestrian corner	1160		Zinc Yellow
•	BCC0-116-00P3 Pedestrian corner	1160		Zinc Yellow Graphite Black
‡	BCM1-116-00P3 Pedestrian mid	1160		Zinc Yellow
#	BCM0-116-00P3 Pedestrian mid	1160		Zinc Yellow Graphite Black
}	BCE1-116-00P3 Pedestrian end	1160		Zinc Yellow
F	BCE0-116-00P3 Pedestrian end	1160		Zinc Yellow Graphite Black

Hand rails 5 articles

ARTICLES / DESCRI	PTION	HEIGHT (MM)	CC (MM)	COLOR
	RCP1-177-0200 Hand rail extrusion		2000	Zinc Yellow
	RCP1-127-0150 Hand rail extrusion, C-C=1500mm, RAL 1018 yellow		1500	Zinc Yellow
	RCP1-077-0100 Hand rail		1000	Zinc Yellow
	RCP1-047-0070 Hand rail		700	Zinc Yellow
	RCP1-027-0050 Hand rail		500	Zinc Yellow

Gate 1 articles

ARTICLES / DESCRIPTION	HEIGHT (MM)	CC (MM)	COLOR
GCP8-069-0121			

Related products



PEDESTRIAN BARRIERS

Pedestrian gate

Universally handed, self closing and width adjustable from 690mm to 1210 mm.

1 articles



CLASSIC PEDESTRIAN BARRIER

Pedestrian with impact high

Use the X-Protect Pedestrian + Impact high barrier configuration to protect walkways from medium duty vehicles where there is a reduced risk of ground level impacts. It is also possible to combine...

19 articles



CLASSIC PEDESTRIAN BARRIER

Pedestrian with impact

Use the X-Protect Pedestrian + Impact barrier configuration to protect walkways from medium duty vehicles where there is an increased risk of ground level impacts. It is also possible to combine wi...

19 articles

Impact Protection



X-Protect is Safe

- ✓ Our impact protection products undergo rigorous testing at our state-of-the-art testing facility.
- ✓ With decades of experience in industrial safety, we've designed our impact protection to perform effectively in real-world conditions.
- ✓ We know safety and can guide you to the best solutions tailored to your specific needs.

X-Protect is **Modular**

- ✓ Quickly modify barrier specifications with minimal waste.
- Perform easy and cost-effective repairs at a component level.
- Quickly build strong integrated installations with few parts.

X-Protect is Sustainable

- Simple end of life dis-assembly, even after an accident.
- ✓ Single material components that are easy to recycle.
- Repairable by design, damaged or worn components are easily replaced extending the barrier's life.



Technical Information



X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Hand Rails



Width x Height:

68 × 72 mm | 2 11/16" × 2 27/32" Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 × 220 mm | 4 9/16" x 8 21/32" Lenath:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Height: 350 - 1160 mm 13 13/16" -45 11/16" Width: 200 mm 7 7/8" in

Component Colours



RAL 1018




RAL 9011

X-Protect Standard Configurations



on the C-C. More information is available upon request.






Impact testing

This is how we calculate the energy from a vehicle impact.








Speed	Load	
6 km/h 3.7 mph	3770 J	
8 km/h 5 mph	6660 J	
12 km/h 7.5 mph	14970 J	

Loaded weight 2100 kg/ 4620 lbs


Speed	Load	
6 km/h 3.7 mph	2930 J	
8 km/h 5 mph	5180 J	
12 km/h 7.5 mph	11670 J	

Operating temperature




























The Floor Barrier can be used in combination with configurations: 3, 6, 8 & 9

- 1. Bollards 2. Impact
- 3. Impact High
- 4. Double Impact Low
- 5. Double Impact High
- 6. Pedestrian
- 7. Pedestrian + Impact
- 8. Pedestrian + Impact High
- 9. Pedestrian +Double Impact
- 10. Pedestrian Gate
- 11. Column Guard
- 12. Floor Barrier