Pedestrian with impact high

Use the X-Protect Pedestrian + Impact high barrier configuration to protect walkways from medium duty vehicles where there is a reduced risk of ground level impacts. It is also possible to combine with a pedestrian gate. The pedestrian gate is self closing, provided with a universal handle and width is adjustable from 690-1210 mm.



X-Protect is a unique approach to safety barriers. Unrivalled modularity, using only a few system components and damping that is built in to create a barrier system that changes with your work place. X-Protect allows rapid transformation, repair or replacement of existing barriers and bespoke configurations are limitless.

Impact test results					
Area of impact	Load	Equivalent to		90° Deflection	Force to fixings
Centre of barrier C -	Centre of barrier C - C as below				
2000mm		2500 kg 9.1 km/h	5000 kg 6.4 km/h	450mm	17 kN
Posts					
End post	118511 1	2500 kg 4.3 km/h	5000 kg 3 km/h	NA *	11.6 kN
Mid post	2450 J	2500 kg 5 km/h	5000 kg 3.5 km/h	NA *	12.7 kN

^{*} Deflection of posts is equivalent or less than that of the rail/s and is not considered to be critical for product selection. Performance is tested at height of the lowest rail. The post will perform better for lower strikes and deflection.

Models

Posts 6 articles

ARTICLES / DESCRIPTION		HEIGHT (MM)	LENGTH (MM)	CC (MM)	COLOR
#	BCC1-116-I1P2 Pedestrian + Impact High corner	1160			Zinc Yellow
-	BCC0-116-I1P2 Pedestrian + Impact High corner	1160			Zinc Yellow Graphite Black
•	BCM1-116-I1P2 Pedestrian + Impact High mid	1160			Zinc Yellow
#	BCM0-116-I1P2 Pedestrian + Impact High mid	1160			Zinc Yellow Graphite Black
ŀ	BCE1-116-I1P2 Pedestrian + Impact High end	1160			Zinc Yellow
	BCE0-116-I1P2 Pedestrian + Impact High end	1160			Zinc Yellow Graphite Black

Impact rails 7 articles

ARTICLES / DESCRIPTION	HEIGHT (MM)	LENGTH (MM)	CC (MM)	COLOR
RCI1-027-00 Impact rail	050	270	500	Zinc Yellow
RCI1-277-03 Impact rail	300	2770	3000	Zinc Yellow
RCI1-227-02 Impact rail	250	2270	2500	Zinc Yellow
RCI1-177-02 Impact rail	200	1770	2000	Zinc Yellow
RCI1-127-01 Impact rail	150	1270	1500	Zinc Yellow
RCI1-077-01 Impact rail	100	770	1000	Zinc Yellow
RCI1-047-00 Impact rail	070	470	700	Zinc Yellow

Hand rails 5 articles

ARTICLES / DESCRIPTION	HEIGHT (MM)	LENGTH (MM)	CC (MM)	COLOR
RCP1-027-0050 Hand rail		270	500	Zinc Yellow
RCP1-047-0070 Hand rail		470	700	Zinc Yellow
RCP1-077-0100 Hand rail		770	1000	Zinc Yellow
RCP1-127-0150 Hand rail		1270	1500	Zinc Yellow
RCP1-177-0200 Hand rail		1770	2000	Zinc Yellow

Gate 1 articles

ARTICLES / DESCRIPTION HEIGHT (MM) LENGTH (MM) CC (MM) COLOR



GCP8-069-0121 Pedestrian gate, 690-1210 mm

Related products



PEDESTRIAN BARRIERS

Pedestrian gate

Universally handed, self closing and width adjustable from 690mm to 1210 mm.

1 articles



CLASSIC PEDESTRIAN BARRIER

Pedestrian with impact

Use the X-Protect Pedestrian + Impact barrier configuration to protect walkways from medium duty vehicles where there is an increased risk of ground level impacts. It is also possible to combine wi...

19 articles



CLASSIC PEDESTRIAN BARRIER

Pedestrian

Use the X-Protect Pedestrian barrier configuration to define pedestrian routes and protect from light duty impacts. It is also possible to combine with a pedestrian gate. The pedestrian gate is sel...

12 articles

Impact Protection



X-Protect is Safe

- ✓ Our impact protection products undergo rigorous testing at our state-of-the-art testing facility.
- ✓ With decades of experience in industrial safety, we've designed our impact protection to perform effectively in real-world conditions.
- ✓ We know safety and can guide you to the best solutions tailored to your specific needs.

X-Protect is **Modular**

- ✓ Quickly modify barrier specifications with minimal waste.
- Perform easy and cost-effective repairs at a component level.
- Quickly build strong integrated installations with few parts.

X-Protect is Sustainable

- Simple end of life dis-assembly, even after an accident.
- ✓ Single material components that are easy to recycle.
- Repairable by design, damaged or worn components are easily replaced extending the barrier's life.



Technical Information



X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Hand Rails



Width x Height:

68 × 72 mm | 2 11/16" × 2 27/32" Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 × 220 mm | 4 9/16" x 8 21/32" Lenath:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Height: 350 - 1160 mm 13 13/16" -45 11/16" Width: 200 mm 7 7/8" in

Component Colours



RAL 1018




RAL 9011

X-Protect Standard Configurations



on the C-C. More information is available upon request.






Impact testing

This is how we calculate the energy from a vehicle impact.








Speed	Load	
6 km/h 3.7 mph	3770 J	
8 km/h 5 mph	6660 J	
12 km/h 7.5 mph	14970 J	

Loaded weight 2100 kg/ 4620 lbs


Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J

Operating temperature




























The Floor Barrier can be used in combination with configurations: 3, 6, 8 & 9

- 1. Bollards 2. Impact
- 3. Impact High
- 4. Double Impact Low
- 5. Double Impact High
- 6. Pedestrian
- 7. Pedestrian + Impact
- 8. Pedestrian + Impact High
- 9. Pedestrian +Double Impact
- 10. Pedestrian Gate
- 11. Column Guard
- 12. Floor Barrier